

Outdoor Radar Dome Air Conditioner



Description

Order Number:	4410918
Brand Name:	Compact Outdoor
Colour:	RAL 7035
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 56
Note:	The unit has an internal MCB (miniature circuit breaker) accessible by removing the front cover
Approvals:	CE

Technical Data


Cooling capacity L35L35 (EN14511-3):	1600 W (L40L45)
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	750 g / 26.5 oz
High / low Pressure:	21 / 6 bar 305 / 88 psig
Operating Temperature Range:	+20°C - +50°C
Air flow volume (system / unimpeded):	Ambient air circuit: 530 / 1200 m³/h Cabinet air circuit: 375 / 550 m³/h
Mounting:	Standalone
Dimensions A x B x C (D+E):	550 x 557 x 500 mm
Weight:	50 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	4.2 A
Starting current:	15.5 A
Max. current:	4.7 A
Nominal power L35L35:	1.02 kW
Fuse:	10 A (T)
Short-circuit current rating:	5 kA
Connection:	2 x 3 m 180 mm flexible plastic duct

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Taric code	84158200
GTIN (EAN)	5350604321816