

Control Cabinet Air Conditioner



Description

Order Number:	43201001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus

Technical Data


Cooling capacity L35L35 (EN14511-3):	2 kW
Cooling capacity L35L50 (EN14511-3):	1.65 kW
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	620 g / 21.9 oz
High / low Pressure:	29 / 6 bar 425 / 88 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit 650 / 1200 m³/h Cabinet air circuit 470 / 850 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	980 x 395 x 260 mm
Weight:	50 kg
Cut out dimensions:	920 x 335 mm
Voltage / Frequency:	120 V ~ 60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current L35L35:	11.2 A
Starting current:	40.1 A
Max. current:	18.8 A
Nominal power L35L35:	1,28 kW
Max. power:	1,42 kW
Fuse:	20 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT INDOOR - reliable and economical](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Stainless steel housing part no.	4320102
With condensate evaporation part no.	43201101
Box dimensions	1,015 x 443 x 295 mm
Gross weight	53.5 kg
Taric code	84158200