

Cooling unit NEMA / Type 4X



Description

Order Number:	57040182
Brand Name:	Compact Outdoor
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4, 4X
Included:	With enclosure heater and aluminium filter
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data


Cooling capacity L35L35 (EN14511-3):	290 W @ 50 Hz 300 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	250 W @ 50 Hz 250 W @ 60 Hz
Enclosure heater:	150 W
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R 134a / 1430
Refrigerant charge:	115 g / 4.05 oz
High / low Pressure:	29.3 / 6.1 bar 425 / 88 psig
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 85 / 300 m³/h Cabinet air circuit: 85 / 136 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	480 x 250 x 190 mm
Weight:	15.2 kg
Cut out dimensions:	204 x 250 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	1.3 A
Starting current:	5 A
Max. current:	1.5 A
Nominal power L35L35:	270 W
Max. power:	325 W
Fuse:	2.5 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

In stainless steel 316 (V4A) part no.	57040184
Box dimensions	530 x 298 x 230 mm
Gross weight	16.5 kg
Taric code	84158200